

# H2O Strip

**Coating & Wax Stripper for Most Tile & Stone Surfaces Including:**

- Ceramic Tile
- Unglazed Ceramic Tile
- Granite
- Slate
- Cement Grout & Mortar
- Quarry Tile
- Porcelain Tile
- Non Polished Marble
- Non Polished Limestone
- Masonry
- Saltillo
- Terra Cotta
- Flagstone
- Cantera
- Brick

**Special Features**

- Fast Acting
- Interior & Exterior
- Water Base Formula
- Less Expensive
- Easy-to-Use
- Low Odor

**PRODUCT DESCRIPTION**

**KEEP OUT OF REACH OF CHILDREN.** H2O Strip is a fast acting, high potency stripper designed to remove wax, acrylic, grease and stains from tile, grout, marble, granite, concrete and masonry surfaces. H2O Strip removes **Miracle Sealants' Mira Shine** when it becomes necessary to strip these products. H2O Strip has a high pH and may adversely affect the polished finish on marble, limestone, travertine and other calcareous stone surfaces.

**Sample Testing**

Due to the differences of each material, several inconspicuous test patches should be completed to assure maximum performance. **User must determine suitability of the product for their intended use.**

**Protect Neighboring Surfaces**

Always protect neighboring surfaces including wood, carpet, metal, landscaping and other masonry and non masonry surfaces.

**APPLICATION INSTRUCTIONS**

Read the entire label and PDS/MSDS before starting. Use from approved container.

**Coating Removal:** Apply H2O Strip directly out of the bottle using a mop or stripper applicator. Allow H2O Strip to stand for 5 - 15 minutes, agitating the surface periodically with a stripping pad or brush. Do not allow to dry on the surface. Multiple applications maybe necessary with difficult areas. Rinse with clean water and remove dirty remains with towels or a wet vacuum system.

**Heavy Wax Build up Removal:** Use approximately 1 part concentrate H2O Strip to 12 parts clean water. Light wax build up & cleaning mix 1 part H2O Strip to 16 - 20 parts water

**Special Notes**

Do not use on polished marble, limestone or other calcium-base surfaces.

Be careful to choose the appropriate stripping pad or brush.

Do not allow to dry on the surface.

**Water, Stain & Slip Protection**

To protect cleaned areas from future soiling, staining and increase static coefficient of friction, we recommend applying the appropriate **Miracle Penetrating Sealer/Impregnator.**

**Color and Gloss Enhancement**

For added color with "Textured and Non polished" surfaces, **511 Seal & Enhance** or **Mira Matte** may be used. For porous type "Paver", **511 Seal & Enhance, Stone Polish, Granite Brite, MiraPolish, Mira Dust, Marble Conditioner** or **Tile Brite** may be used as directed.

**Heavy Duty Cleaning:** Use **Phosphoric Acid Cleaner** , **GCFR** or **Liquid Poultice** as directed.

**Light Cleaning:** Use **Mira Clean #1, Porcelain & Ceramic Tile Cleaner, Tile & Grout Cleaner, Mira Soap** and **Counter Kleen** as directed.

**Coverage**

Coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface and application methods. Used as directed, **H2O Strip** will cover approximately 200 - 300 square feet per gallon (18 - 27 square meters per 3.785 liters).

**MAINTENANCE**

For ongoing maintenance instructions please refer to **Miracle Sealants Care Guide.** Refer to the **Miracle Sealants Product Recommendation Chart** for specific product recommendations.

**Storage**

Store **H2O Strip** in the original container, properly sealed to avoid contamination. Stored at 77° F (40° C), **H2O Strip** will have a shelf life of 12 months. Do not allow to freeze.

**Technical Support**

For additional technical support, contact Miracle Sealants Company at 1-800-350-1901 or 626-443-6433 ext. 3013

**Office Hours**

Monday - Friday from 8:30 am - 5:00 pm PT.  
1-626-443-6433 or 1-800-350-1901 • Fax: 1-626-443-1435  
website: www.miraclesealants.com

**Product Damaged During Transportation**

If product is damaged during transportation contact Info Trac @ 1-800-535-5053

**Additional Products**

Miracle Sealants Company offers a complete line of water & stain repellents, sealers, cleaner, polishing compounds, diamond abrasives, machinery and accessories for the tile, stone, concrete, metal, fabric and carpet professional or do-it yourself specialist.

**Caution**

**H2O Strip** contains sodium hydroxide and 2-Butoxy ethanol. Avoid contact with eyes, mucous membranes and skin. Do not inhale or swallow. Use in a well ventilated area. Good ventilation means fresh air is flowing in such a way as to feel a slight breeze. Continue to ventilate until odors are completely eliminated. Inhaling odors can be harmful. Keep away from heat and open flames. Avoid prolonged contact with skin. Keep small children and pets out of the area until products or surfaces has thoroughly dried. **Refer to MSDS for additional information.**

**Warranty**

Instructions are a condensed guide and should not be considered complete. In the event of failure, the only obligation of Miracle Sealants Company shall be to replace such products proven to be defective. **Before using, user shall determine the suitability of the product for their intended use. User assumes all risks and liability whatsoever in connection therein.** Neither seller nor manufacturer shall be liable for any injury or inability to use this product.

# H2O Strip

**Osha's Hazard Communication Standard  
U.S. Department Of Labor**

29 CFR 1910.1200 OMB No. 1218-0072  
Identity No: Name: H2o Strip

**Section 1**

Manufacturers Name: Miracle Sealants Company  
Address: 12318 Lower Azusa Road  
Emergency Phone: 800-350-1901  
City: Arcadia  
State: CA  
Phone: 626-443-6433  
Date Prepared: March 2008

**Section 2 - Hazardous Ingredient/Identity Information**

Hazardous Components	CAS #	OSHA PEL	ACGIH TLV
2 (Butoxy) Ethanol	112-34-5	25 ppm	25 ppm
Sodium Hydroxide	131-073-2	2mg/m3	2 mg/m3
2-Amino-Ethanol	141-43-5	3 ppm	3 ppm

VOC : 8% by weight (non-regulated)

**Section 3 - Physical/Chemical Characteristics**

Boiling point: > 212°F Specific gravity: 1.07  
Vapor pressure: Not tested Melting point: Not tested  
Vapor density: Not tested Evaporation rate: Not tested  
Solubility in water: 100%

Appearance and odor: Yellow, solvent odor

**Section 4 - Fire and Explosion Hazard Data**

Flash point: Not Available Flammable limits: Not tested  
LEL: Not tested UEL: Not tested  
pH: 12-13  
NFPA hazard rating (0 = Least, 4 = Extreme)  
Health: 2 Fire: 0  
Reactivity: 0 Other: 0  
HMIS Hazard Rating:  
Health: 2 Fire: 0  
Reactivity: 0

Extinguishing media: CO<sub>2</sub>, dry foam  
Special fire fighting procedures: None  
Unusual fire and explosion hazards: None

**Section 5 - Reactivity Data**

Stability: Stable  
Conditions to avoid: None  
Incompatible materials to avoid: Strong oxidizers, ammonia.  
Hazardous decomposition or byproducts: CO, CO<sub>2</sub>  
Hazardous polymerization: Will not occur.

**Section 6 - Health Hazard Data****Routes of Entry:**

Eyes - Possible  
Inhalation - Possible  
Skin - Possible  
Ingestion - Possible  
Health Hazards - Same as signs and symptoms of exposure.

**Carcinogenicity:**

OSHA: None NTP: None  
IARC Monographs: None

**Signs and Symptoms of Over Exposure**

Eyes: Burning sensation  
Skin: Irritation  
Ingestion: Burning irritation  
Inhalation: Dizziness, headaches, irritation

Medical conditions generally aggravated by exposure: None known.

**Emergency and First Aid Procedures:**

**Eyes:** Flush with water for 15 minutes. If irritation persists, call physician  
**Skin:** Wash off with soap and water. If irritation persists, call physician.  
**Ingestion:** Do not induce vomiting. Call physician or Poison Control Center immediately.  
**Inhalation:** Get person to fresh air. If unconscious, call a physician.

**Section 7 - Precautions For Safe Handling And Use**

Steps to be taken in case material is released or spilled: Soak up with inert material. Scoop up and place in a proper waste disposal method: Dispose of in accordance with federal, state and local regulations.

Precautions to be taken in handling and storing: store in a cool, dry place, out of direct sunlight. Do not freeze equal to or less than 32° F or heat above 110° F.

Other precautions: KEEP OUT OF REACH OF CHILDREN. Follow directions on the container for proper use of this product.

**Section 8 - Control Measures**

Respiratory protection: Ventilate by opening all doors and windows. If exposure above the TLV or PEL require a NIOSH approved respirator equipped for the exposure or suitable respiratory protection per 29 CFR 1910.134 is required.

**Ventilation:**

Local exhaust - If available Special - None  
Mechanical - If available Other - None

Protective gloves: Plastic or rubber, chemical resistant.

Eye protection: Tight fitting, splash proof safety glasses.

Other protective clothing or equipment: Chemical resistant clothing.

Work hygienic practices: Wash hands thoroughly before handling food stuffs, liquids or tobacco products. Use common sense and care around chemicals. Never mix this product with other chemicals. Consult your supervisor for all other hygienic and safety practices. All practices depend on your specific business. Directions for use normally found on label which will dictate engineering and control measures.

**Section 9 - Shipping & Regulatory Classification**

DOT Shipping Name: Please refer to the Bill of Lading receiving/documents for up-to-date information.

DOT#: Not Available DOT Hazard Class: Not Available

Toxic Substances Control Act (TSCA): This product and/or all the ingredients contained in this product have been registered under the Toxic Substances Control Act.

Contains (Butoxy) Ethanol

**SARA:** No SARA 313 chemicals identified.

**NOTE:** Miracle Sealants believes the data set forth are accurate. Miracle Sealants makes no warranty with respects thereto and disclaims all liability or reliance thereon. Such data are offered solely for consideration, investigation and verification. Also, the data set forth is for the concentrated finished product. All lab samples are for experimental purposes only and used at the customers discretion.